Printing date 02/07/2012

Reviewed on 02/06/2012

· Product identifier

- Trade name: 196 (color shades black, red)
- Relevant identified uses of the substance or m ixture and uses advised against: -• Application of the substance / the preparation: stamp pad ink
- · Details of the supplier of the safety data sheet:

Manufacturer/Supplier
 Noris-Color GmbH
 Ziegelhüttener Str.1
 Germany-95326 Kulmbach
 Phone: +49(0) 9221 - 92 00 0
 Fax : +49(0) 9221 - 92 00 90

Distributor: Specialty Ink Company, Inc. 20 Dunton Avenue Deer Park, NY 11729 USA Phone: 631-586-3666 Fax: 631-586-3874

· Emergency telephone number: 800-688-4005, Veolia acct #4180

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC F Highly flammable
- · Hazard description: F Highly flammable
- · Information concerning particular hazards for human and environment:
- The product has to be labelled due to the calculation procedure of international guidelines. Has a narcotizing effect.
- R11 Highly flammable.
- R 67 Vapours may cause drowsiness and dizziness
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· Label elements

• Labelling according to EU guidelines: The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:



F Highly flammable

· Risk phrases:

- 11 Highly flammable.
- 67 Vapours may cause drowsiness and dizziness

```
· Safety phrases:
```

- 2 Keep out of the reach of children.
- 7/9 Keep container tightly closed and in a well-ventilated place.

18 Handle and open container with care.

20/21 When using do not eat, drink or smoke.

24/25 Avoid contact with skin and eyes.29/56 Do not empty into drains, dispose of this material and its

container at hazardous or special waste collection point

```
· Classification system:
```

```
• NFPA ratings (scale 0 - 4)
Health = 0
Fire = 3
Reactivity = 0
```

```
HMIS-ratings (scale 0 - 4)
Health = 0
Fire = 3
Reactivity = 0
```

(Contd. on page 2)

Printing date 02/07/2012

Reviewed on 02/06/2012

Trade nam e: 196 (color shades black, red)

 $(Contd. \ of \ page \ 1)$

- · Personal Protection letter: B
- Results of PBT and vPvB assessment • PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

• Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous

additions. • 1	additions. · Dangerous components:			
64-17-5	ethanol	50-100%		
1569-02-4	1-ethoxypropan-2-ol	10-25%		
107-98-2	1-methoxypropan-2-ol	2.5-10%		

• Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Wash with water and soap.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist consult doctor.
- After swallowing: Rinse mouth with water(only if person conscious). If symptoms persist consult doctor.
- Information for doctor:
- $\cdot \textit{Most important symptoms and effects, both acute and delayed No further relevant information available.}$
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Firefighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- \cdot For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- \cdot Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Prevent seepage into sewage system, workpits and cellars.
- Inform respective authorities in case of seepage into water course or sewage
- system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Printing date 02/07/2012

Reviewed on 02/06/2012

Trade nam e: 196 (color shades black, red)

(Contd. of page 2)

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the

workplace: 64-17-5 ethanol

PEL 1900 mg/m³, 1000 ppm

REL 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

107-98-2 1-methoxypropan-2-ol

REL Short-term value: 540 mg/m³, 150 ppm

Long-term value: 360 mg/m³, 100 ppm TLV Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Wash hands before breaks and at the end of work.

· Breathing equipment: Not required.

· Protection of hands:

Protective Gloves recommended during refilling/handling larger quantities.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Printing date 02/07/2012

Reviewed on 02/06/2012

Trade nam e: 196 (color shades black, red)

(Contd. of page 3) • Eye protection: Tightly sealed goggles recommended during refilling/handling larger quantities.

9 Physical and chemical property	ies
· Information on basic physical and ch	nemical
properties · General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
• Odor:	Characteristic
• Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78°C (172 °F)
· Flash point:	12°C (54 °F)
· Flam m ability (solid, gaseous):	-
· Ignition temperature:	255°C (491 °F)
• Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
• Explosion limits:	
Lower:	1.3 Vol %
Upper:	15.0 Vol %
• Vapor pressure at 20°C (68 °F):	59 hPa (44 mm Hg)
· Density:	Not determined.
• Relative density	Not determined.
• Vapour density	Not determined.
• Evaporation rate	Not determined.
• Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
• Segregation coefficient (n-octonol/wa	ater): Not determined.
• Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	70.0 - 80.0 %
Water:	<1 %
VOC content:	70.0 - 80.0 %
Solids content:	20 .0 - 30.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 5)

(Contd. of page 4)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 02/07/2012

Reviewed on 02/06/2012

Trade nam e: 196 (color shades black, red)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

- Acute toxicity:
- · Primary irritant effect:
- \cdot on the skin: No irritant effect.
- \cdot on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- \cdot Additional ecological information:
- General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- Waste disposal key: recommendation 080111 (waste containing organic solvents)
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
\cdot UN proper shipping name		
\cdot DOT, IMDG, IATĂ	PAINT	
·ADR	1263 PAINT	

USA

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 02/07/2012

Reviewed on 02/06/2012

Trade nam e: 196 (color shades black, red)

		(Contd. of page
• Transport hazard class(es)		
· DOT, IMDG, IATA		
CHANGE LCD		
• Class	3 Flammable liquids.	
· Label	3	
· Class	3 Flammable liquids	
• Label	3	
· Packing group		
· DOT, ADR, IMDG, IATA	II	
• Environmental hazards:		
• Marine pollutant:	No	
• Special precautions for user	Warning: Flammable liquids	
• Danger code (Kemler):	33	
• EMS Number:	<i>F-E,<u>S-E</u></i>	
• Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact: Noris-Color GmbH; laboratory/product safety; info@noris-color.de

PDF to Word